

# bastion



DISPOSABLE GLOVES

Latex Powder Free Micro Textured



# bastion

Ultimate solutions in barrier protection

T 0800 864 725 F 0800 864 725 E [sales@bastionpacific.co.nz](mailto:sales@bastionpacific.co.nz)  
W [www.bastionpacific.co.nz](http://www.bastionpacific.co.nz)



# Latex Powder Free Micro Textured

<b>Product:</b>	Latex Powder Free Smooth
<b>Material:</b>	Natural Rubber Latex
<b>Type:</b>	Non Sterile
<b>Design:</b>	Ambidextrous
<b>Cuff:</b>	Beaded
<b>Usage:</b>	Single Use Only
<b>Colour:</b>	Beige
<b>Packaging:</b>	100 ± 2 pcs/inner, 10 inners/carton

## Dimensions:

Size	Palm Width (mm)	MGM Length (mm)	ASTM D3578-05 Length (mm)
S	80-89	Min. 240	Min. 220
M	90-99	Min. 240	Min. 230
L	100-109	Min. 240	Min. 230
XL	110-119	Min. 240	—

## Thickness:

Location of Thickness Measurement	Single Wall (mm)
Finger	Min. 0.15
Palm	Min. 0.15
Cuff	Min. 0.10

## Physical Properties:

	Before Aging	After Aging
Tensile Strength (MPa)	Min. 18	Min. 14
Elongation (%)	Min. 650	Min. 500
Modulus (500%)	Max. 5.5 MPa	—
Force At Break (N)	Min. 9	Min. 6

<b>Protein Content:</b>	Max. 50µg/dm <sup>2</sup>
<b>Powder Level:</b>	Max. 2mg/ dm <sup>2</sup>
<b>Compliance Standards:</b>	ASTM D3578-05, EN 455 Part 1,2 & 3: 2000

## Inspection Criteria: (Sampling & Inspection ISO 2859)

	Inspection Level	AQL
Watertight Test	G1	1.5
Major Defects	G1	2.5
Minor Defects	G1	4.0
Dimensions	S2	4.0
Physical Properties	S2	4.0

## Quality Assurance:

ISO 9001: 2000 Certified by SGS (UK) and SIRIM (Malaysia)

ISO 13485: 2003 Certified by SGS (UK)

Directive 89/686/EEC on Personal Protective Equipment Article 11B Certified by SGS (UK)

